

TECHNICAL SPECIFICATIONS



W 3, W 10

W 3 and W 10 are plastic cabinet public address loudspeakers with build-in 100V transformer.

Simply mounting and power adjustment taps allow flexible and quick mounting these loudspeakers on the wall or other vertical surfaces. Frequency range from 200 Hz to 15 kHz presents these wall loudspeakers for public announcements systems in the schools, hospitals, offices or other public places. These loudspeakers are suitable for music background systems too.

	W 3	W 10
Rated power	3 W	10 W
Transformer power taps at 100 V	3 W - 1,5 W - 0,75 W	10 W - 5 W - 2,5 W
Sensitivity	84 dB (1 W/1 m)	87 dB (1 W/1 m)
Maximum SPL	93 dB (Pmax /1 m) at 1860 Hz	101 dB (Pmax/1 m) at 1815 Hz
Frequency response	200 Hz – 15 kHz	200 Hz – 15 kHz
Dispersion at 1000 Hz	180° (H) x 180° (V)	180° (H) x 180° (V)
Driver dimensions	4" (101 mm)	4" (101 mm)
Dimensions	185 mm x 190 mm x 90 mm	185 mm x 190 mm x 90 mm
Weight	0,6 kg	0,7 kg
Material	ABS plastic	ABS plastic
Colour	White (RAL 9016)	White (RAL 9016)

unit: mm

W series

