6 W, 5" ceiling loudspeaker EN 54, ABS dome

Part-No.: 582411

The 5" broadband loudspeaker chassis, which is impregnated against humidity, distinguishes itself by way of its high degree of effectiveness. Typically, the 6 W, 3 W, or 1.5 W power setting can be selected. The spring latch (2 pieces) guarantees an uncomplicated and quick mounting onto the ceiling. The ABS dome enables easy wiring. The speaker contains a ceramic terminal and a thermal fuse.

Rated Power	6 W
Transformer power taps	6/3/1.5 W
Rated impedance	1
Sensitivity EN 54-24, 1 W / 1 m	89 dB
Sensitivity EN 54-24, max 1 m	96 dB
Transmission range	100 Hz ... 20000 Hz
Ambient temperature	-25 °C ... 55 °C
Storage temperature	-40 °C ... 70 °C
Material	Plastic
Color	white, similar to RAL 9003
Weight	approx. 0.82 kg
Cut-out size	(Ø min.) 164 mm
Dimensions	Ø: 180 mm D: 110 mm

Subject to change without notice! © 2020 Honeywell International Inc.

Novar GmbH a Honeywell Company
Forumstr. 30 41468 Neuss
Phone: +49 2131 40615 600
Faximile: +49 2131 40615 606
www.esser-systems.com
info@esser-systems.com